# Safety Data Sheet (SDS)

www.HMTsolder.com

To comply with European CLP Regulation 1272/2008, US 29CFR 1910.1200 OSHA's Hazard Communication Standard, and Australian NOHSC: 1008 [2004] and ADG Code 7.4

#### 1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: NanoCoat3000/NanoCoat3000UV

**SYNONYMS:** Nano Coating, Thin Coat, Conformal Coating

PART NUMBERS: NanoCoat3000-2-30cc, NanoCoat3000-4-30cc, NanoCoat3000-10-30cc, NanoCoat3000-2-400ml, NanoCoat3000-4-

400ml, NanoCoat3000-10-400ml, NanoCoat3000-2-1L, NanoCoat3000-4-1L, NanoCoat3000-10-1L, NanoCoat3000-2-1GAL, NanoCoat3000-4-1GAL, NanoCoat3000-4-5GAL, NanoC

NanoCoat3000-4-1GAL, NanoCoat3000-10-1GAL, NanoCoat3000UV-2-5GAL, NanoCoat3000UV-4-5GAL, NanoCoat3000UV-10-30cc, NanoCoat3000UV-2-400ml, NanoCoat3000UV-4-400ml, NanoCoat3000UV-10-400ml, NanoCoat3000UV-2-1L, NanoCoat3000UV-4-1L, NanoCoat3000UV-10-1L, NanoCoat3000UV-2-1GAL, NanoCoat3000UV-4-1GAL, NanoCoat3000UV-4-5GAL, NanoCoat3000UV-10-1GAL, NanoCoat3000UV-4-5GAL, NanoCoat3000UV-10-5GAL

MANUFACTURER: HMT Solder Inc.

ADDRESS: 357 Lang Blvd, Grand Island, NY 14072 (USA)

8-1500 Sandhill Dr., Ancaster, ON L9G 4V5 (Canada)

**PHONE**: (800) 717-2786

EMERGENCY PHONE: (800) 424-9300 (USA and Canada 24/7 CHEMTREC)

**REVISION DATE:** 2022/06/01

REVISION NUMBER: 1.0

REVISED BY: HMT Solder Product Safety

PRODUCT USE: PCB Coating

#### 2. HAZARD IDENTIFICATION

Classified in accordance with European CLP Regulation 1272/2008

Aquatic Chronic 4 H413

CHEMICAL NAME: NA
CHEMICAL FAMILY: Mixture
CHEMICAL FORMULA: Proprietary

ROUTES OF ENTRY: Inhalation, Ingestion, Skin/Eye Contact

TARGET ORGANS: NA

GHS/CLP:



Signal Word: Warning

TARGET ORGANS: NA

#### **GHS/CLP LABEL ELEMENTS:**

Hazard statement(s)

H336 May cause drowsiness or dizziness.

H413 May cause long lasting harmful effects to aquatic life.

Precautionary statement(s)

P271 Use in a well-ventilated area.
P273 Avoid release to the environment.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

## **POTENTIAL HEALTH EFFECTS:**

**EYE CONTACT:** May cause moderate irritation. Do not allow material to come in contact with eyes.

SKIN CONTACT: No additional information available.

INHALATION: May cause irritation to the respiratory tract.

INGESTION: May be fatal if swallowed and enters airways.

CHRONIC: Not established.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE: No additional information available.

#### **SECTION 2 NOTES:**

HMT Solder Inc. does not recommend, manufacture, market, or endorse any of its products for human consumption.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Classified in accordance with European CLP Regulation 1272/2008

Name	Product Identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
1,1,2,2-Tetrafluoroethyl-2,2,2- trifluoroethyl ether	(CAS-No.) 406-78-0	80-95	H336 H413
Fluoroacrylate	Proprietary	0.1-10	Not Classified

### SECTION 3 NOTES:

This formulation does not contain PFOA or PFOS and is not derived from compounds comprising these materials. The components of this product are in compliance with the chemical notification requirements of TSCA. All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS) or are exempt polymers whose monomers are listed on EINECS.

### 4. FIRST-AID MEASURES

EYES: Flush with plenty of water, contact a physician. If contact lenses can be removed easily, flush eyes without contact lenses.

SKIN: Wash affected area with plenty of warm, soapy water. If irritation persists, seek medical attention.

INGESTION: Rinse mouth. Drink 1 or 2 glasses of water. Do not induce vomiting without medical advice. Get immediate medical attention.

**INHALATION:** Remove person to fresh air. Thermal decomposition occurs at prolonged time at temperatures above 300°C. Effects of breathing thermal decomposition products may include coughing, sneezing, shortness of breath, and chest tightness. If thermal decomposition products have been inhaled, get immediate medical attention.

#### 5. FIREFIGHTING MEASURES

**EXTINGUISHING MEDIA:** Water Spray, Dry chemical, foam, Carbon dioxide

SPECIAL FIRE FIGHTING PROCEDURES: When fire-fighting conditions are severe and total thermal decomposition of the product is possible, wear full

protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head. Exposure to decomposition products may be a hazard to health. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Evacuate personnel to safe areas. Cool containers/tanks with water spray. Residues and contaminated fire

extinguishing water must be disposed of in accordance with local regulations.

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Exposure to extreme heat can cause thermal decomposition. Carbon Monoxide, Carbon Dioxide, Hydrogen Fluoride, Fluorinated Hydrocarbons, Carbonyl Fluoride, Carbon oxides, Hydrogen Chloride.

#### **6. ACCIDENTAL RELEASE MEASURES**

**ACCIDENTAL RELEASE MEASURES:** If material spills or leaks, remove traces of residue using absorbent sand or earth. Exposure to spilled material may be irritating. Follow on-site personal protective equipment recommendations.

ENVIRONMENTAL PRECAUTIONS: Avoid release to the environment. Collect spillage.

#### **SECTION 6 NOTES:**

See Sections 2, 4, and 7 for additional information.

#### 7. HANDLING AND STORAGE

**HANDLING/STORAGE:** Keep containers tightly closed when not in use. Use care to avoid spills. Avoid inhalation of fumes. Avoid contact witheyes, skin, and clothing. Store in a closed corrosive resistant container, with corrosive resistant liner, in cool dry place. Wear appropriate personal protective equipment when working with or handling. Always wash hands thoroughly after handling this product. Dispose of following Federal, State/Provincial, and Local regulations.

**OTHER PRECAUTIONS:** Empty containers may retain product residues in vapor, liquid, and/or solid form. All labeled hazard precautions should be observed.

WORK HYGIENIC PRACTICES: Cosmetics/Food/Drink/Tobacco should not be consumed or used in work areas. Always wash hands after handling material and before applying or using cosmetics/food/drink/tobacco.

### **SECTION 7 NOTES:**

For industrial use only. Keep out of reach of children. Not for internal consumption.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### **OCCUPATIONAL EXPOSURE LIMIT VALUES:**

Ingredient	CAS No.	Limit Type
1,1,2,2-Tetrafluoroethyl-2,2,2-	yl-2,2,2- 406-78-0 AEL: 50ppm (8hr-TWA)	
trifluoroethyl ether		EEL: 150ppm (1hr-TWA)

**ENGINEERING CONTROLS:** Provide appropriate local exhaust when product is heated.

VENTILATION: Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLVs.

**RESPIRATORY PROTECTION:** A (US: NIOSH; EU: EN 140:1998, EN 14387:2004 A)-approved air-purifying respirator with fume/organic chemical cartridge should be worn when airborne concentrations may be exceeded. General and local exhaust ventilation is the preferred means of protection.

EYE PROTECTION: Use with appropriate eye protection: Goggles or face shield (EU: EN 166-S 3 9).

SKIN PROTECTION: Protective gloves (solvent resistant) should be worn when the possibility of skin contact exists (EU: EN 374-1:2003).

PROTECTIVE CLOTHING OR EQUIPMENT: Wear suitable protective clothing.

**WORK HYGIENIC PRACTICES:** Cosmetics/Food/Drink/Tobacco should not be consumed or used in areas where solder products may be used. Always wash hands after handling solvents and before applying or using cosmetics/food/drink/tobacco.

**OTHER:** Maintain eye wash stations in work areas. Avoid the use of contact lenses in high fume areas. Clean protective equipment regularly. Clean up spills immediately.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE Liquid **APPEARANCE:** Colorless ODOR: Fther-like **ODOR THRESHOLD:** Not Established pH as SUPPLIED: Neutral **MELTING POINT:** Not Established FREEZING POINT: Not Established **INITIAL BOILING POINT:** 61°C (100.4°F) **BOILING RANGE:** 61-62 °C **FLASH POINT:** None 49 (BUOAC=1) **EVAPORATION RATE: VAPOR PRESSURE:** 269 hPa **RELATIVE DENSITY:** 1.5-1.6 g/ml SOLUBILITY IN WATER: Slightly Soluble 405 °C **AUTOIGNITION TEMPERATURE:** VISCOSITY: No Data

#### 10. STABILITY AND REACTIVITY

STABILITY: Stable

CONDITIONS TO AVOID (STABILITY): Not Established

INCOMPATIBILITY (MATERIAL TO AVOID): Strong Acids, Strong Bases, Strong Oxidizing agents

HAZARDOUS DECOMPOSITION/BY-PRODUCTS: Exposure to extreme heat can cause thermal decomposition. Carbon Monoxide, Carbon Dioxide,

Hydrogen Fluoride, Fluorinated Hydrocarbons, Carbonyl Fluoride, Carbon oxides, Hydrogen

Chloride.

## 11. TOXICOLOGICAL INFORMATION

#### INHALATION:

Vapors from heated material may cause irritation of the respiratory system. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

#### SKIN

Contact with skin during product use is not expected to result in significant irritation.

#### EYES:

Exposure to heated material may cause Eye Irritation.

#### **ACUTE TOXICITY:**

Product/Ingredient Name	Result	Species	Dose	Exposure
1,1,2,2-Tetrafluoroethyl-	LD50 Oral	Rat	2000mg/kg	-
2,2,2-trifluoroethyl ether	LD50 Dermal			

SKIN CORRISION/IRRITATION:
SERIOUS EYE DAMAGE/IRRITATION:
RESPIRATORY OR SKIN SENSITIZATION:
GERM CELL MUTAGENICITY:
CARCINOGENICITY:
Not Established
Not Mutagenic
Not Established

**REPRODUCTIVE TOXICITY:** Not toxic to female or male reproduction.

STOT-SINGLE EXPOSURE: Not Established STOT-REPEATED EXPOSURE: Not Established ASPIRATION HAZARD: Not Established

#### 12. ECOLOGICAL INFORMATION

Ecotoxicity:No Data AvailablePersistence and degradability:No Data AvailableBioaccumulative potential:No Data AvailableMobility in Soil:No Data AvailableOther Adverse Effects:No Data Available

**WASTE DISPOSAL METHOD:** Scrap and waste should be recycled or stored in a dry, sealed container for later disposal. Disposal must be in accordance with Federal, State/Provincial, and Local Regulations.

#### 13. DISPOSAL INFORMATION

**Disposal Methods**: Should be taken to authorized industrial waste handler.

**Uncleaned Packaging**: Dispose of as unused product according to official regulations.

#### 14. TRANSPORT INFORMATION

Transport in accordance with applicable regulations and requirements.

UN Number: Not available
UN Proper Shipping Name: Not available
Packaging Group: Not applicable
Environmental Hazards: None

#### TRANSPORT HAZARD CLASSES:

US DOT Hazardous Material Classification:
Water Transportation:
Non-Hazardous
Non-Hazardous
Non-Hazardous
Non-Hazardous
Non-Hazardous
Not regulated
Not regulated
ADG Land Transportation
Not regulated
Not regulated

#### 15. REGULATORY INFORMATION

All ingredients used to manufacture this product are listed on the EPA TSCA Inventory. Finished product is not listed on the EPA TSCA Inventory.

U.S. FEDERAL REGULATIONS:
STATE REGULATIONS:
INTERNATIONAL REGULATIONS:
AUSTRALIAN REGULATIONS:
Not regulated
Not regulated
Not regulated

#### **16. OTHER INFORMATION**

LEGEND:

ACGIH American Conference of Governmental Industrial Hygienists

ADG Australian Dangerous Goods Code

ADR European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS Australian Inventory of Chemical Substances

BCF Bioconcentration factor
C.A.S. Chemical Abstract Service

**CLP** Classification, Labeling and Packaging

DOT Department of Transportation
EC Effective Concentration
EPA Environmental Protection Agency
GHS Global Harmonized System

HMIS
IARC
International Agency for Research on Cancer
IATA
International Air Transport Association
IMDG
International Maritime Dangerous Goods Code

LC Lethal Concentration

LD Lethal Dose
NA Not available
NE Not established

NIOSH National Institute for Occupational Safety & Health

NOEC No observed effective concentration

NOHSC National Occupational Health and Safety Commission (Australia)

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit
Pow Octanol water partition coefficient

SDS Safety Data Sheet

STEL Short-Term Exposure Limit
STOT Specific target organ toxicity
TLV Threshold Limit Value
TSCA Toxic Substance Control Act
TWA: Time Weighted Average

**US DOT:** United States Department of Transportation

#### PREPARATION INFORMATION:

This update supersedes all previously released documents.

#### DISCLAIMER

The information and recommendations contained within this publication have been compiled from sources believed to be reliable and to represent the best information available to HMT Solder at the time of issue. No warranty, guarantee, or representation is made by HMT Solder nor does HMT Solder assume any responsibility in connection there within; nor can it be assumed that all acceptable safety measures or other safety measures may not be required under particular or exceptional conditions or circumstances. The data on this Safety Data Sheet relates only to this product and does not relate to use with any other material or in any process. All chemical products should be used only by, or under the direction of, technically qualified personnel who are aware of the hazards involved and necessity for reasonable care in handling. Hazard communication regulations require that employees must be trained on how to use a Safety Data Sheet as a source for hazard information.

Copyright © 2020-2022 HMT Solder™ Inc.